Grease Interceptor Service Monitoring Log

Business Name:

Comments:

Comments:



□Yes □No

□Yes □No



Access Code:

| Cleaning is required every 30 days or before the grease and solids combined reach 25% of the liquid capacity, whichever comes first. For all self-cleaned interceptors, before and after photos must be submitted within 7 days of cleaning to sourcecontrol@sylvanlake.ca. | | | | | | | | | |
|---|--------------------------------|-----------|---------|---------------------------------------|---|---|--|-------------------|-----------------------------------|
| Cleaning and monitoring records are required to be kept onsite for a minimum of two (2) years and be available upon request. | | | | | | Self-Cleaned | | | Third-Party |
| Date (yyyy/mmm/dd) | Location of Grease Interceptor | Inspected | Cleaned | Bottom Solids Depth (inches) | Floating Grease Depth (inches) | Name of owner/ staff performing inspection/ cleaning | Before/ after photos taken and submitted? | Disposal location | Licensed service provider name |
| / / | | | | " | " | | □Yes □No | | |
| Comments: Online self-reporting complete? | | | | | | | | | |
| / / | | | | " | " | | □Yes □No | | |
| Comments: | | | | | | | | | |
| / / | | | | " | " | | □Yes □No | | |
| Comments: | | | | | | | | | |
| / / | | | | " | " | | □Yes □No | | |
| Comments: | | | | | | | | | |

Business License #: